

Centrifugal Regenerative Pumps (Self Priming)



FEATURES

Compact, Efficient and reliable in operation
Designed to operate under wide voltage fluctuations
Require very simple maintenance
Trouble free service
Need not use Foot valve

APPLICATIONS

Pumps water from sumps and shallow wells
One can lift the pump anywhere they wish
Car Washing
Small raise buildings
Gardening and Fountains



CONSTRUCTION

Extruded aluminum body / CI body
Powder coated
Impeller : Gun Metal
Inbuilt Thermal Overload Protector
Seal : Ceramic & Graphite
Self lubricated double ball bearings



S. No.	HP	KW	TYPE	Pipe Size (mm)	Discharge in LPM	Head in Metres														
						3	6	9	12	15	18	21	24	27	30	33	36	39	42	
1.	0.5	0.37	BR2K	25 x 25	45	45	40	34	30	27	24	22	20	17	15					
2.	0.5	0.37	BR2KH	25 x 25		45	40	34	30	27	24	22	20	17	15					
3.	0.5	0.37	BR2KE	25 x 25	25	25	23	21	14	12	10									
4.	1.0	0.75	BR1K	25 x 25		56	54	51	47	43	40	36	33	29	26	24	20	18	16	
5.	1.0	0.75	BR1ECO	25 x 25	50	47	43	40	37	36	34	33	28	25	23	20	16	13		

The above performances are based on a means supply voltage of 220 V - 1 ph 50 Cycles.